

CMP462: Natural Language Processing



Lecture 03: Spelling Correction

Mohamed Alaa El-Dien Aly
Computer Engineering Department
Cairo University
Spring 2013

Agenda

- Spelling correction
- Noisy Channel Model
 - Language Model
 - Error Model

Acknowledgment:

Most slides adapted from Chris Manning and Dan Jurafsky's NLP class on [Coursera](#).



Spelling Correction and the Noisy Channel

The Spelling Correction Task



Applications for spelling correction

Word processing

Phones

Web search



Spelling Tasks

- Spelling Error Detection
- Spelling Error Correction:
 - Autocorrect
 - hte → the
 - Suggest a correction
 - Suggestion lists



Types of spelling errors

- Non-word Errors
 - *graffe* → *giraffe*
- Real-word Errors
 - Typographical errors
 - *three* → *there*
 - Cognitive Errors (homophones)
 - *piece* → *peace*,
 - *too* → *two*




Non-word spelling errors

- Non-word spelling error detection:
 - Any word not in a **dictionary** is an error
 - The larger the dictionary the better
- Non-word spelling error correction:
 - Generate **candidates**: real words that are similar to error
 - Choose the one which is best:
 - Shortest weighted edit distance
 - Highest noisy channel probability



Real word spelling errors

- For each word w , generate candidate set:
 - Find candidate words with similar *pronunciations*
 - Find candidate words with similar *spelling*
 - Include w in candidate set
- Choose best candidate
 - Noisy Channel
 - Classifier




Spelling Correction and the Noisy Channel

The Noisy Channel
Model of Spelling




Noisy Channel Intuition





Noisy Channel Intuition





Noisy Channel

- We see an observation x of a misspelled word
- Find the correct word w

$$\hat{w} = \operatorname{argmax}_{w \in V} P(w | x)$$

$$= \operatorname{argmax}_{w \in V} \frac{P(x | w)P(w)}{P(x)}$$

$$= \operatorname{argmax}_{w \in V} P(x | w)P(w)$$

Language Model
Term

Channel/Error Modeling
Term



History: Noisy channel for spelling proposed around 1990

- **IBM**

- Mays, Eric, Fred J. Damerau and Robert L. Mercer. 1991. Context based spelling correction. *Information Processing and Management*, 23(5), 517–522

- **AT&T Bell Labs**

- Kernighan, Mark D., Kenneth W. Church, and William A. Gale. 1990. A spelling correction program based on a noisy channel model. Proceedings of COLING 1990, 205-210



Non-word spelling error example

acress



Candidate generation

- Words with similar spelling
 - Small edit distance to error
- Words with similar pronunciation
 - Small edit distance of pronunciation to error



Damerau-Levenshtein edit distance

- Minimal edit distance between two strings, where edits are:
 - Insertion
 - Deletion
 - Substitution
 - Transposition of two adjacent letters



Words within distance 1 of `acress`

Error	Candidate Correction	Correct Letter	Error Letter	Type
<code>acress</code>	<code>actress</code>	<code>t</code>	<code>-</code>	deletion
<code>acress</code>	<code>cress</code>	<code>-</code>	<code>a</code>	insertion
<code>acress</code>	<code>caress</code>	<code>ca</code>	<code>ac</code>	transposition
<code>acress</code>	<code>access</code>	<code>c</code>	<code>r</code>	substitution
<code>acress</code>	<code>across</code>	<code>o</code>	<code>e</code>	substitution
<code>acress</code>	<code>acres</code>	<code>-</code>	<code>s</code>	insertion
<code>acress</code>	<code>acres</code>	<code>-</code>	<code>s</code>	insertion



Candidate generation

- 80% of errors are within edit distance 1
- Almost all errors within edit distance 2
- Also allow insertion of **space** or **hyphen**
 - thisidea → this idea
 - inlaw → in-law



Language Model $P(w)$

- Use any of the language modeling algorithms we've learned
- Unigram, bigram, trigram
- Web-scale spelling correction
 - Stupid backoff



Unigram Prior probability

Counts from 404,253,213 words in Corpus of Contemporary American English (COCA)

word	Frequency of word	P(word)
actress	9,321	.0000230573
gress	220	.0000005442
caress	686	.0000016969
access	37,038	.0000916207
across	120,844	.0002989314
acres	12,874	.0000318463



Channel model probability $P(x|w)$

- **Error model probability, Edit probability**
- *Kernighan, Church, Gale 1990*
- Look at letter errors:
 - *Misspelled word* $x = [x_1, x_2, x_3 \dots x_m]$
 - *Correct word* $w = [w_1, w_2, w_3 \dots, w_n]$
- $P(x|w)$ = probability of the edit
 - (deletion/insertion/substitution/transposition)



Computing error probability: confusion matrix

`del[x,y]:` `count(xy typed as x)`
`ins[x,y]:` `count(x typed as xy)`
`sub[x,y]:` `count(x typed as y)`
`trans[x,y]:` `count(xy typed as yx)`

Insertion and deletion conditioned on previous character



Confusion matrix for spelling errors

sub[X, Y] = Substitution of X (incorrect) for Y (correct)

X	Y (correct)																									
	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
a	0	0	7	1	342	0	0	2	118	0	1	0	0	3	76	0	0	1	35	9	9	0	1	0	5	0
b	0	0	9	9	2	2	3	1	0	0	0	5	11	5	0	10	0	0	2	1	0	0	8	0	0	0
c	6	5	0	16	0	9	5	0	0	0	1	0	7	9	1	10	2	5	39	40	1	3	7	1	1	0
d	1	10	13	0	12	0	5	5	0	0	2	3	7	3	0	1	0	43	30	22	0	0	4	0	2	0
e	388	0	3	11	0	2	2	0	89	0	0	3	0	5	93	0	0	14	12	6	15	0	1	0	18	0
f	0	15	0	3	1	0	5	2	0	0	0	3	4	1	0	0	0	6	4	12	0	0	2	0	0	0
g	4	1	11	11	9	2	0	0	0	1	1	3	0	0	2	1	3	5	13	21	0	0	1	0	3	0
h	1	8	0	3	0	0	0	0	0	0	2	0	12	14	2	3	0	3	1	11	0	0	2	0	0	0
i	103	0	0	0	146	0	1	0	0	0	0	6	0	0	49	0	0	0	2	1	47	0	2	1	15	0
j	0	1	1	9	0	0	1	0	0	0	0	2	1	0	0	0	0	0	5	0	0	0	0	0	0	0
k	1	2	8	4	1	1	2	5	0	0	0	0	5	0	2	0	0	0	6	0	0	0	4	0	0	3
l	2	10	1	4	0	4	5	6	13	0	1	0	0	14	2	5	0	11	10	2	0	0	0	0	0	0
m	1	3	7	8	0	2	0	6	0	0	4	4	0	180	0	6	0	0	9	15	13	3	2	2	3	0
n	2	7	6	5	3	0	1	19	1	0	4	35	78	0	0	7	0	28	5	7	0	0	1	2	0	2
o	91	1	1	3	116	0	0	0	25	0	2	0	0	0	0	14	0	2	4	14	39	0	0	0	18	0
p	0	11	1	2	0	6	5	0	2	9	0	2	7	6	15	0	0	1	3	6	0	4	1	0	0	0
q	0	0	1	0	0	0	27	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
r	0	14	0	30	12	2	2	8	2	0	5	8	4	20	1	14	0	0	12	22	4	0	0	1	0	0
s	11	8	27	33	35	4	0	1	0	1	0	27	0	6	1	7	0	14	0	15	0	0	5	3	20	1
t	3	4	9	42	7	5	19	5	0	1	0	14	9	5	5	6	0	11	37	0	0	2	19	0	7	6
u	20	0	0	0	44	0	0	0	64	0	0	0	0	2	43	0	0	4	0	0	0	0	2	0	8	0
v	0	0	7	0	0	3	0	0	0	0	0	1	0	0	1	0	0	0	8	3	0	0	0	0	0	0
w	2	2	1	0	1	0	0	2	0	0	1	0	0	0	0	7	0	6	3	3	1	0	0	0	0	0
x	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	9	0	0	0	0	0	0	0
y	0	0	2	0	15	0	1	7	15	0	0	0	2	0	6	1	0	7	36	8	5	0	0	1	0	0
z	0	0	0	7	0	0	0	0	0	0	0	7	5	0	0	0	0	2	21	3	0	0	0	0	3	0



Generating the confusion matrix

- [Peter Norvig's list of errors](#)
- [Peter Norvig's list of counts of single-edit errors](#)



Channel model

Kernighan, Church, Gale 1990

$$P(x|w) = \begin{cases} \frac{\text{del}[w_{i-1}, w_i]}{\text{count}[w_{i-1} w_i]}, & \text{if deletion} \\ \frac{\text{ins}[w_{i-1}, x_i]}{\text{count}[w_{i-1}]}, & \text{if insertion} \\ \frac{\text{sub}[x_i, w_i]}{\text{count}[w_i]}, & \text{if substitution} \\ \frac{\text{trans}[w_i, w_{i+1}]}{\text{count}[w_i w_{i+1}]}, & \text{if transposition} \end{cases}$$



Channel model for access

Candidate Correction	Correct Letter	Error Letter	$x w$	$P(x word)$
actress	t	-	c ct	.000117
gress	-	a	a #	.00000144
caress	ca	ac	ac ca	.00000164
access	c	r	r c	.000000209
across	o	e	e o	.00000093
acres	-	s	es e	.0000321
acres	-	s	ss s	.0000342



Noisy channel probability for `acress`

Candidate Correction	Correct Letter	Error Letter	$x w$	$P(x word)$	$P(word)$	$10^{-9} * P(x w)P(w)$
actress	t	-	c ct	.000117	.0000231	2.7
cress	-	a	a #	.00000144	.000000544	.00078
caress	ca	ac	ac ca	.00000164	.00000170	.0028
access	c	r	r c	.000000209	.0000916	.019
across	o	e	e o	.0000093	.000299	2.8
acres	-	s	es e	.0000321	.0000318	1.0
acres	-	s	ss s	.0000342	.0000318	1.0



Noisy channel probability for across

Candidate Correction	Correct Letter	Error Letter	$x w$	$P(x word)$	$P(word)$	$10^{-9} * P(x w)P(w)$
actress	t	-	c ct	.000117	.0000231	2.7
cress	-	a	a #	.00000144	.000000544	.00078
caress	ca	ac	ac ca	.00000164	.00000170	.0028
access	c	r	r c	.000000209	.0000916	.019
across	o	e	e o	.0000093	.000299	2.8
acres	-	s	es e	.0000321	.0000318	1.0
acres	-	s	ss s	.0000342	.0000318	1.0




Using a bigram language model

- "a stellar and versatile **actress** whose combination of sass and glamour.."
- Counts from the Corpus of Contemporary American English with add-1 smoothing
- $P(\text{actress}|\text{versatile}) = .000021$ $P(\text{whose}|\text{actress}) = .0010$
- $P(\text{across}|\text{versatile}) = .000021$ $P(\text{whose}|\text{across}) = .000006$
- $P(\text{"versatile actress whose"}) = .000021 * .0010 = 210 \times 10^{-10}$
- $P(\text{"versatile across whose"}) = .000021 * .000006 = 1 \times 10^{-10}$



Using a bigram language model

- "a stellar and versatile **actress** whose combination of sass and glamour.."
- Counts from the Corpus of Contemporary American English with add-1 smoothing
- $P(\text{actress}|\text{versatile}) = .000021$ $P(\text{whose}|\text{actress}) = .0010$
- $P(\text{across}|\text{versatile}) = .000021$ $P(\text{whose}|\text{across}) = .000006$
- $P(\text{"versatile actress whose"}) = .000021 * .0010 = 210 \times 10^{-10}$
- $P(\text{"versatile across whose"}) = .000021 * .000006 = 1 \times 10^{-10}$



Evaluation

- Some spelling error test sets
 - [Wikipedia's list of common English misspelling](#)
 - [Aspell filtered version of that list](#)
 - [Birkbeck spelling error corpus](#)
 - [Peter Norvig's list of errors \(includes Wikipedia and Birkbeck, for training or testing\)](#)



Spelling Correction and the Noisy Channel

Real-Word Spelling Correction



Real-word spelling errors

- ...leaving in about fifteen *minuets* to go to her house.
- The design *an* construction of the system...
- Can they *lave* him my messages?
- The study was conducted mainly *be* John Black.
- 25-40% of spelling errors are real words [Kukich 1992](#)




Solving real-word spelling errors

- For each word in sentence
 - Generate *candidate set*
 - the word itself
 - all single-letter edits that are English words
 - words that are homophones
- Choose best candidates
 - Noisy channel model
 - Task-specific classifier





Noisy channel for real-word spell correction

- Given a sentence $w_1, w_2, w_3, \dots, w_n$
- Generate a set of candidates for each word w_i
 - Candidate(w_1) = $\{w_1, w'_1, w''_1, w'''_1, \dots\}$
 - Candidate(w_2) = $\{w_2, w'_2, w''_2, w'''_2, \dots\}$
 - Candidate(w_n) = $\{w_n, w'_n, w''_n, w'''_n, \dots\}$
- Choose the sequence W that maximizes $P(W)$




Noisy channel for real-word spell correction





Noisy channel for real-word spell correction





Simplification: One error per sentence

- Out of all possible sentences with one word replaced
 - w_1, w'_2, w_3, w_4 two **off** thew
 - w_1, w_2, w'_3, w_4 two of **the**
 - w''_1, w_2, w_3, w_4 **too** of thew
 - ...
- Choose the sequence W that maximizes $P(W)$



Where to get the probabilities

- Language model
 - Unigram
 - Bigram
 - Etc
- Channel model
 - Same as for non-word spelling correction
 - Plus need probability for no error, $P(w|w)$



Probability of no error

- What is the channel probability for a correctly typed word?
- $P(\text{"the"} \mid \text{"the"})$
- Obviously this depends on the application
 - .90 (1 error in 10 words)
 - .95 (1 error in 20 words)
 - .99 (1 error in 100 words)
 - .995 (1 error in 200 words)



Peter Norvig's "thew" example

x	w	x w	$P(x w)$	$P(w)$	$10^9 P(x w)P(w)$
thew	the	ew e	0.000007	0.02	144
thew	thew		0.95	0.00000009	90
thew	thaw	e a	0.001	0.0000007	0.7
thew	threw	h hr	0.000008	0.000004	0.03
thew	thwe	ew we	0.000003	0.00000004	0.0001



Spelling Correction and the Noisy Channel

State-of-the-art Systems



HCI issues in spelling

- If very confident in correction
 - Autocorrect
- Less confident
 - Give the best correction
- Less confident
 - Give a correction list
- Unconfident
 - Just flag as an error



State of the art noisy channel

- We never just multiply the prior and the error model
- Independence assumptions \rightarrow probabilities not commensurate
- Instead: Weigh them

$$\hat{w} = \operatorname{argmax}_{w \in V} P(x | w) P(w)^\lambda$$

- Learn λ from a development test set




Phonetic error model

- Use pronunciation
- Metaphone, used in GNU aspell
 - Convert misspelling to metaphone pronunciation
 - “Drop duplicate adjacent letters, except for C.”
 - “If the word begins with 'KN', 'GN', 'PN', 'AE', 'WR', drop the first letter.”
 - “Drop 'B' if after 'M' and if it is at the end of the word”
 - ...
 - Find words whose pronunciation is 1-2 edit distance from misspelling’s
 - Score result list
 - Weighted edit distance of candidate to misspelling
 - Edit distance of candidate pronunciation to misspelling pronunciation



Improvements to channel model

- Allow richer edits (context) (Brill and Moore 2000)
 - ent → ant
 - ph → f
 - le → al
- Incorporate pronunciation into channel (Toutanova and Moore 2002)



Channel model

- Factors that could influence $p(\text{misspelling} | \text{word})$
 - The source letter
 - The target letter
 - Surrounding letters
 - The position in the word
 - Nearby keys on the keyboard
 - Homology on the keyboard
 - Pronunciations
 - Likely morpheme transformations



Nearby keys





Classifier-based methods for real-word spelling correction

- Instead of just channel model and language model
- Use many features in a classifier (e.g. MaxEnt classifiers).
- Build a classifier for a specific pair like:

whether/weather

- “cloudy” within +/- 10 words
- ___ to VERB
- ___ or not

Recap

- Spelling correction
- Noisy Channel Model
 - Language Model
 - Error Model